

VISTA EVO

VISTA-EV06
SAP CODE: 2002346

Well rounded LED batten.

VISTA EVO is a sleek new concept on a traditional design. This well rounded batten may have a small footprint but packs all the features that is expected from a VISTA product. Available in black or white, 2ft or 4ft and optional emergency and motion sensors round out this simple yet reliable LED batten.


APPLICATIONS

Garage, Shed, Offices, Education Facilities, Storage Facilities, Storage Rooms, Manufacturing Facilities, Temporary Installations

DIMENSION DIAGRAMS



PHOTOMETRIC DIAGRAM



Unit: cd
 - C0/180 140.4deg
 - C90/270 109.3deg
 Photometric diagram shown is for 4000K output.

KEY INFORMATION

Power	10 W 13 W 17 W 20 W
Lumen Output	1310 / 1383 / 1335 lm 1622 / 1746 / 1671 lm 2054 / 2254 / 2108 lm 2313 / 2582 / 2383 lm
Mounting Type	Surface Mount
Dimming Type	Non-Dimmable
Fascia Colour	White RAL 9003
IP Rating	IP20
IK Rating	Not Applicable
Operating Ambient Temp.	-20 to 45°C
Connection Type	PA14 Terminals
Driver	Integrated
Warranty	5 yrs

PHOTOMETRIC

Efficacy	10W: 124 / 135 / 125 lm/W 13W: 121 / 135 / 123 lm/W 17W: 115 / 132 / 116 lm/W 20W: 111 / 129 / 111 lm/W
CCT	4000 / 4700 / 5700 K
CRI	> 80
SDCM	< 3
UGR	> 25
Beam Angle	120°
Flicker-Free	Yes
Lifespan	>50,000hrs @ Ta 25°C (L80)

ELECTRICAL

Input Voltage	220-240Vac, 50/60Hz
Power Factor	> 0.9
Electrical Classification	Class I
Surge Protection	Overload / Short Circuit

OTHERS

Body Material	Steel
Diffuser Material	Polycarbonate (Opal)
Cable Entry	Rear & Ends
Rebate Scheme Approvals	Not Applicable
HACCP Approval	No
Weight	0.72 kg
Dimensions	605 x 64 x 65 mm

Disclaimer

NOTE1: SDCM Value measured at 4K & 5.7K CCT